



Codo 90°, Roscado / SW



ROSCADO THREADED									
NW Pulg.	2000Lb			3000Lb			6000Lb		
	A mm.	BØ mm.	Peso~ Kg%	A mm.	BØ mm.	Peso~ Kg%	A mm.	BØ mm.	Peso~ Kg%
1/4	24,5	25,5	14	24,5	25,5	14	28,5	33,5	30
3/8	24,5	25,5	12,5	28,5	33,5	27	33,5	38	45,5
1/2	28,5	33,5	22	33,5	38	41,5	38	46	72
3/4	33,5	38	32	38	46	65	44,5	55,5	115,5
1	38	46	47	44,5	55,5	103,5	51	62	161,5
1 1/4	44,5	55,5	74	51	62	130,5	60,5	75,5	267
1 1/2	51	62	92,5	60,5	75,5	221,5	63,5	84	320,5
2	60,5	75,5	153,5	63,5	84	247	86	110	794
2 1/2	76	92	298	86	110	734	95,5	120,5	985
3	86	110	454	95,5	120,5	778	114,5	152,5	1.800
4	114,5	152,5	1.328	114,5	152,5	1.328	---	---	---

Codo 90° , Roscado / SW



S. W. - ENCHUFE Y SOLDADURA										
NW	3000Lb					6000Lb				
	A	B \emptyset	D \emptyset	E	Peso	A	B \emptyset	D \emptyset	E	Peso
Pulg.	mm.	mm.	mm.	mm.	Kg%	mm.	mm.	mm.	mm.	Kg%
1/4	24,5	25,5	14	13,5	12	---	---	---	---	---
3/8	24,5	25,5	17,5	11	10,4	---	---	---	---	---
1/2	28,5	33,5	21,7	12,5	21,8	33,5	38	21,7	14,5	40
3/4	33,5	38	27,1	14,5	30,8	38	46	27,1	16	62,1
1	38	46	33,8	16	46,7	44,5	55,5	33,8	17,5	102,1
1 1/4	44,5	55,5	42,6	17,5	67,1	51	62	42,6	19	132,1
1 1/2	51	62	48,7	19	90,2	60,5	75,5	48,7	22	237
2	60,5	75,5	61,1	22	136,1	63,5	84	61,1	22	272,4
2 1/2	76	92	73,8	34,5	280	86	110	73,8	30	580
3	86	110	89,8	29	440	95,5	120,5	89,8	32	840
4	114,5	152,5	115,4	48	1.330	114,5	152,5	115,4	35	1.580



Valvulas Industriales de Toluca S.A. de C.V.

Av. Emiliano Zapata, Esquina Altamiranos S/N,
Col. Emiliano Zapata, C.P. 52000,
Lerma Estado de México, Tel. (728) 284 7200
Fax (728) 282 2226 Nextel Ventas 52*107-42*76
vitventas@vitsa.com.mx
www.vitsa.com.mx